



Vehicle livery guidelines

Your vehicle livery quote is based on the following criteria.

1. Vehicles must be clean, dry and free from dirt, but not polished or waxed before application of vinyl or paint.
2. Vehicles must be in a well lit area with the vehicle not exposed to strong sunlight, heavy rain or windy conditions.
3. Some adhesives require additional measures for the material to bond to vehicle panels. These may include but are not limited to:
 - a) Enclosure of vehicle in undercover facilities with temperature of at least 12°C overnight, prior to the day of application.
 - b) Enclosure of vehicle in undercover facilities with temperature of at least 12°C, at least twelve hours after application is complete.

Additional costs will be incurred if:

4. Vehicles are not clean and dry for vinyl application or removal.
5. Additional cleaning of vehicle other than standard surface preparation, ie: removal of existing vinyl films, gum residue, tar, and stubborn dirt.
6. Vehicle not available for agreed work at agreed time and date.
7. Inadequate working environment resulting in additional labour.
8. Waste created from the vehicle livery application will be disposed of, in site facilities' designated bins or removed by Barry Robertson.
9. 240v power supply is required for some vinyl application and removal processes.

These measures are recommended to fulfill the expected finish and durability of your vehicle graphics and to eliminate materials failure.

Attention and care is involved in every vehicle livery application and removal.

In the event of accidental damage, Barry Robertson will not be held responsible for loss or damage to vehicle paint surfaces, loss or damage to removal of vehicle badges, mouldings, trims, or vehicle fixtures in any vinyl application or vinyl removal process unless proven otherwise.